



## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

KOSAKI et al.

Application No.

09/986,325

Filed: November 8, 2001

Art Unit: 2814

Examiner: A. Chambliss

For:

SEMICONDUCTOR DEVICE

## PENDING CLAIMS

6. A semiconductor device comprising:

a semiconductor substrate having first and second main surfaces, having a semiconductor element in the first main surface, and having a peripheral surface contacting the first and second main surfaces;

a heat radiation layer on the second main surface of the semiconductor substrate; and a flange including a plurality of metal layers disposed on the peripheral surface of the substrate, the metal layers comprising:

a first metal layer having a surface layer containing palladium on a side toward the first main surface;

a second metal layer of a nickel-based alloy contacting the surface layer containing palladium of the first metal layer, the second metal layer having a topmost portion located below and spaced from the first main surface; and

a third metal layer disposed under the first metal layer.

- 7. The semiconductor device according to claim 6, wherein the third metal layer comprises a nickel-based alloy layer, a gold layer, and a laser-cut metal layer including one of a nickel layer and a chromium layer.
- 8. The semiconductor device according to claim 7, wherein the third metal layer is selected from the group consisting of a single layer of gold, and a plurality of layers including a titanium layer and a gold layer, on the laser-cut metal layer.

In re Appln. of KOSAKI et al. Application No. 09/986,325

- 9. The semiconductor device according to claim 6, wherein the first metal layer comprises one selected from the group consisting of a palladium layer and a titanium layer under the palladium layer, and a single layer.
- 10. The semiconductor device according to claim 6, wherein the second metal layer is selected from the group consisting of Ni-P alloy, Ni-B alloy, and Ni-B-W alloy.